

Exploring the New Frontier of EV Industry



SUPREME MEGA SHAKTI

AB MEGA SAVINGS DEGA



SUPREME SHAKTI

HEAVY DUTY
Shocker

Robust
Body



**HALF
BODY
LOADER**
Driver + 500 kg

**Expand Your Possibilities:
Extra Load Space, Extra Savings**

SUPREME SUPER SHAKTI

Stay High and Dry with 300 mm Ground Clearance –

Rain or Shine, Your Safety's in Line !

ZYADA
Space

BADA
Windshield



5
KA DUM



**Strong
& Durable**



**Long Life
Battery**



3*
Years
**Pan India
Service**



35
Paisa
Max Cost/KM



Easy Charging

**FULL
BODY
LOADER**

Driver + 500 kg

SUPREME SUPER DLX

SOLID
Chromium Steel

DABANG
Body

- Roof Carrier
- Rear Shocker
- Music System
- Cabin Light
- Fire Stop
- Bottle Stand



BADA
Tyre



SUPREME SUPER DLX



SUPREME ECO



SUPREME DLX

Experience the Driving Like Never Before with a 30% Increase in Tyre Width for Unparalleled Grip and Control on Roads

SUPREME CLEAN



Easy Maintenance



Eco - Friendly

DRY
Waste

WET
Waste



**Boasting a Modular
Design for Optimal
Efficiency in the
Waste Management
System**



**GARBAGE
DUMPER**

Driver + 600 kg

TECHNICAL SPECIFICATIONS

Variant	Mega shakti	Supreme DLX, Shakti, Clean
Vehicle Category	L5 Full Body Cargo	L3 Passenger, Loader, Garbage
Loading Capacity	600 kgs	400 Kgs
Vehicle Dimensions and Weight		
Length(mm)	3310	2790
Width(mm)	1485	990
Height(mm)	2180	1790
Ground Clearance (mm)	205	180
Wheel Base(mm)	2195	2140
GVW (kgs)	1185	784
Kerb Weight (kgs)	585	309
Cargo Size (Cu.Ft)	145	NA
Turning Radius	3.5	2.8
Chassis	Monocoque	CR Tubes
Tyre Size(Inch)	4.50 * 10	3.75 * 12
Performance		
Running Distance (km)	130-150	100-110
Top Speed (KmpH)	50	25
Gradibility (%)	19	18
Battery		
Operating Voltage (V)	51.2	48
Battery Energy (kWh)	10.75	6.24
Battery Connection	Single	4 / 1 batteries
Capacity (Ah)	210	130
Battery Type	Li-on / LFP	Lead Acid / Li
Charging Time (Hours)	3-5 hours	6-8 hours
Drivetrain		
Transmission Type	Direct Coupler with Motor Manual (Manual dual speed)	Differential Direct Coupling with Motor
Motor type	PMSM DC Motor	BLDC Motor
Control Principle	Open Loop	Open Loop
Voltage Range	42V to 58V	40V to 56V
Peak Current	120 ± 15A	40 ± 15A
Suspension & Brakes		
Front Suspension	Coil spring with Independent Telescopic Shock Absorber	Dual Telescopic Shock Absorber
Rear Suspension	Rubber Damper with Independent Telescopic Shock Absorber	Leaf Spring with Telescopic Shock Absorber
Parking Brake	Mechanical Type	Mechanical Type
Front & Rear Brakes	Hydraulic Drum Brake	Drum Brake

 **SUPREME**
Thinking Green

 **SUPREME**
Thinking Green

 **SUPREME**
Thinking Green

SUPREME SMART POWER PVT. LTD.

Your Trusted Source for Unrivalled Quality Products.



FINANCE FACILITY AVAILABLE PAN INDIA



BANSAL CREDITS LTD.

CONTACT WITH US :

CONTACT NO.:
+91 1244015885
+91 8750093888

TOLL FREE NO.
1800-212-2553

www.supremeev.in
www.supremeglobalgroup.com

**Office No.12 , Old Delhi Road Opp. Maruti Factory Gate No. 2,
Gurgaon, Haryana - 122015**

*T&C Apply