

# AB E - DLX

KE SANG, BADLE SAFAR KA  
RANG



*Supreme E DLX*

### Technical Specifications

Variant	E - DLX
Vehicle Category	L5 M (Passenger)
Seating Capacity	6 + 1
<b>Vehicle Dimensions and Weight</b>	
Length(mm)	3155
Width(mm)	1465
Height(mm)	1920
Ground Clearance (mm)	205
Wheel Base(mm)	2195
GVW (kgs)	1068
Kerb Weight (kgs)	536
Turning Radius	3.5
Chassis	Monocoque
Tyre Size (Inch)	4.50 * 10
<b>Performance</b>	
Running Distance (km)	140-160
Top Speed (KmpH)	50
Gradability (%)	19
<b>Battery</b>	
Operating Voltage (V)	51.2
Battery Energy (kWh)	10.75
Battery Connection	Single
Capacity (Ah)	210
Battery Type	Li-on / LFP
Charging Time (Hours)	3-5 hours
<b>Drivetrain</b>	
Transmission Type	Direct Coupler with Motor Manual (Manual dual speed)
Motor type	PMSM DC Motor
Power (kW)	5.434
Max. Power Output	5.301 kW @ 47 kmph
Control Principle	Open Loop
Voltage Range	42V to 58V
Peak Current	120 ± 15A
<b>Suspension &amp; Brakes</b>	
Front Suspension	Coil spring with Independent Telescopic Shock Absorber
Rear Suspension	Rubber Damper with Independent Telescopic Shock Absorber
Front & Rear Brakes	Hydraulic Drum Brake